



PART NO.	COLOR
MINI-1	BLACK
MINI-1(R)	RED
MINI-1(Y)	YELLOW
MINI-1(G)	GREEN
MINI-1(BU)	BLUE

- NOTE: 1. Current Rating : 1 Amp
 2. Current Voltage : 30V RMS Max
 3. Dielectric Withstanding : AC 500V min Per minute.
 4. Insulation Resistance : 1000M ohms Min At DC 500V
 5. Contact Resistance : 30M ohms Max
 6. Operating Temperature : -45°C ~ +105°C
 7. Insertion force : 0.5Kgf/pin MAX.
 8. Withdrawal force : 0.1Kgf/pin MIN.
 9. Plating : Gold/Nickel Plated



康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO., LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN
 THIS DRAWING IS THE SOLE PROPERTY
 OF KANG YANG HARDWARE
 ENTERPRISE CO. ANY
 REPRODUCTION IN PART OR AS A
 WHOLE WITHOUT THE WRITTEN
 PERMISSION OF
 KANG YANG HARDWARE ENTERPRISE
 CO. IS PROHIBITED.

DATE
 2005.10.28

DRAWN
 JASON

CHECKED
 李柏翳

APPROVED
 Kang

TITLE
 PITCH 2.54mm MINI JUMP

MATERIAL
 PBT UL94V-0+GF

TERMINAL MATERIAL
 BRASS

COLOR
 SEE ABOVE

DWG. NO.
 MINI-1

PART NO.
 SEE ABOVE

SIZE
 A4

SCALE: 5:1

SPEC. DWG

UNIT
 mm

REV
 C

SHEET 1 OF 1

DO NOT SCALE DRAWING