


PART NO.	TAPPED	MARK
PCB-102	M3x0.5P	M3
PCB-102(M4)	M4x0.7P	M4

- NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.
 鍍錫最佳使用時間，為製造日起3個月內。
 2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.
 表面為鍍錫，未使用完畢時，產品請密封。
 3. SUGGEST RATED CURRENT: 15A
 建議額定電流：15A



康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED.

DATE
2018.10.02

DRAWN
Louis

CHECKED
林祺翔

APPROVED
[Signature]

TITLE
P.C.B TERMINAL

MATERIAL
BRASS

COLOR
FINISH
TIN PLATED

UNLESS OTHERWISE SPECIFIED
TOLERANCE: SEE ABOVE

DWG. NO.
PCB-102

PART NO.
SEE ABOVE

SIZE
A4

SPEC. DWG.

REV
B

SCALE: 3:1 UNIT mm

SHEET 1 OF 1

DO NOT SCALE DRAWING