








MOUNTING HOLE
(RECOMMEND FOR REFERENCE ONLY)

PART NO.	FINISH
PCB10AM4NI	NICKEL PLATED
PCB-10AM4	MATTE TIN PLATED

- NOTE: 1. THE BEST USE TIME FOR NICKEL PLATED PARTS ARE WITHIN 6 MONTHS SINCE MFG DATE.
鍍鎳最佳使用時間，為製造日起6個月內。
2. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.
鍍錫最佳使用時間，為製造日起3個月內。
3. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.
未使用完畢時，產品請密封。
4. LOAD CURRENT: 15A.
負載電流值15A.



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE 2008.04.25	TITLE P.C.B TERMINAL	DWG. NO. PCB-10AM4		PART NO. SEE ABOVE	
	DRAWN BUNNY	MATERIAL BRASS	SIZE A4		SPEC. DWG.	
	CHECKED Yuping	COLOR FINISH SEE ABOVE	SCALE: 3:1		UNIT mm	REV A
	APPROVED Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE	SHEET 1 OF 1			