




MOUNTING HOLES

NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.

鍍錫最佳使用時間，為製造日起3個月內。

2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.

表面為鍍錫，未使用完畢時，產品請密封。

3. SUGGEST RATED CURRENT: 15A

建議額定電流：15A



康揚企業股份有限公司  
KANG YANG HARDWARE ENTERPRISE CO., LTD.  
康揚塑膠(東莞)有限公司  
KANG YANG PLASTIC(DONG GUAN)CO., LTD.  
康哲電腦配件(吳江)有限公司  
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED.

DO NOT SCALE DRAWING

DATE  
2004.02.17

DRAWN  
S.L

CHECKED  
李柏賓

APPROVED  
Kang

TITLE  
P.C.B TERMINAL

MATERIAL  
SEE ABOVE

COLOR  
SEE ABOVE

FINISH  
SEE ABOVE

UNLESS OTHERWISE SPECIFIED  
TOLERANCE: SEE ABOVE

DWG. NO.  
PCB-4(632)F

PART NO.  
PCB-4(632)F

SIZE  
A4

SPEC. DWG

REV  
A

SCALE: 3:1 UNIT mm

SHEET 1 OF 1