



RECOMMEND MOUNTING HOLE
RECOMMEND THICKNESS: 1.6mm

NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.

鍍錫最佳使用時間，為製造日起3個月內。

2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.

表面為鍍錫，未使用完畢時，產品請密封。

3. SLIGHT DEFORMED IS NORMAL STATUS.

輕微變形為正常現象。

4. LOAD CURRENT: 10A.

負載電流值10A。



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC (DONG GUAN) CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS (WUJIANG) CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE 2009.06.29	TITLE P.C.B TERMINAL		DWG. NO. PCFS156A		PART NO. PCFS156A	
	DRAWN JIM	MATERIAL BRASS		SIZE A4		SPEC. DWG.	
	CHECKED 李柏青	COLOR	FINISH TIN PLATED				
	APPROVED Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE		SCALE: 5:1		UNIT mm	REV B SHEET 1 OF 1