



MOUNTING HOLE

- NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.
 鍍錫最佳使用時間，為製造日起 3 個月內。
 2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.
 表面為鍍錫，未使用完畢時，產品請密封。
 3. SUGGEST RATED CURRENT: 10A.
 建議額定電流：10A.



康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO., LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN
 THIS DRAWING IS THE SOLE PROPERTY
 OF KANG YANG HARDWARE
 ENTERPRISE CO. ANY
 REPRODUCTION IN PART OR AS A
 WHOLE WITHOUT THE WRITTEN
 PERMISSION OF
 KANG YANG HARDWARE ENTERPRISE
 CO. IS PROHIBITED.

DO NOT SCALE DRAWING

DATE
2014.06.12
 DRAWN
Emily
 CHECKED
林祺翔
 APPROVED
Kang

TITLE
P.C.B TERMINAL
 MATERIAL
BRASS
 COLOR
FINISH
TIN PLATED
 UNLESS OTHERWISE SPECIFIED
 TOLERANCE: SEE ABOVE

DWG. NO.
PCFS250L

PART NO.
PCFS250L

SIZE
A4

SPEC. DWG.

REV
A

SCALE: 4:1

UNIT
mm

SHEET 1 OF 1