



MOUNTING HOLE $\phi 1.0^{+0.1}_{-0}$

PART NO.	L
TEST-26	8.5
TEST-28	10.0

- NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.
 鍍錫最佳使用時間, 為製造日起3個月內。
 2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.
 表面為鍍錫, 未使用完畢時, 產品請密封。



康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	TITLE		DWG. NO.		PART NO.					
	2002.11.21	TEST PIN		TEST-26		SEE ABOVE					
	DRAWN	MATERIAL		SIZE		SPEC. DWG.		REV			
	JASON	BRASS									
	CHECKED		COLOR	FINISH	A4	UNIT		mm		SHEET 1 OF 1	
			TIN PLATED								
	APPROVED	UNLESS OTHERWISE SPECIFIED		SCALE: 5:1							
		TOLERANCE: SEE ABOVE									