


成型尺寸	公差
5mm 以下	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm 以上	±1.0

REVISIONS			
REV	DESCRIPTION	DATE	BY
B	修改模子, 變更尺寸, 公差	2004.11.23	James
C	修改模子, 變更尺寸	2005.07.15	James
D	舊模換新模	2006.11.30	BUNNY



PART NO.	A	B	C	D	E	F	G
TM-2S6	14.9	9.5	5.5	7.0	3.7	7.2	4.0
TM-2S8	14.9	9.5	5.6	7.8	4.5	7.2	4.0
TM-3S8	△ 22.0	△ 16.0	△ 9.2	△ 8.0	4.5	△ 9.6	△ 5.4
TM-3S10	△ 22.0	△ 16.0	9.2	9.6	△ 4.8	△ 9.6	△ 5.4
TM-3S25	△ 22.0	△ 16.0	9.2	△ 12.7	6.4	△ 9.6	△ 5.4

QMF22 Component - Plastics
E I DUPONT DE NEMOURS & CO INC
ENGINEERING POLYMERS CHESTNUT RUN PLAZA PO BOX 80713 WILMINGTON DE 19880

Wednesday, September 15, 2004

E41938

Material Designation: 101(+)(f1), 101F(+)(f1), 101L(+)(f1), E101(+)(f1), E101L(f1), 132F(+)(f1), 135F(+)(f1)
Product Description: Polyamide 66 (PA66), designated "Zytel" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.71	V-2	4	0	130	75	85	725	960
	1.5	V-2	3	0	130	75	85	750	960
	3	V-2	2	0	130	75	85	800	960
	6	V-2	2	0	130	75	85	800	960

CTI: 0 HVTR: 0 D495: 6

Dielectric Strength (KV/mm): 13

ISO Tensile Strength (MPa): -

ISO Tensile Impact (kJ/m²): -

(+) Virgin and regrind up to 50% by weight inclusive, have the same basic material characteristics.

(f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" or "MIN" or "ZEN" or "DEL" or "CRA" or "RYN".

Report Date: 7/29/1996

Underwriters Laboratories Inc®

UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 東莞康揚塑膠五金電子廠 DONG GUAN KANG YANG PLASTIC HARDWARE COMPANY 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO.,LTD.				TITLE 束線帶固定座		產品規格圖面	
				MATERIAL NYLON 66 UL94V-2		DATE 2005.07.15	
				FINISH		DRAWN SCOTT	
				COLOR NATURAL		CHECK 高建和	
PART NUMBER SEE ABOVE		DRAWING NUMBER TM-XSXX		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE		APPROVED Kang	
SIZE A4	SCALE NONE	UNIT mm	REV D				