




NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.

鍍錫最佳使用時間, 為製造日起3個月內.

2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.

表面為鍍錫, 未使用完畢時, 產品請密封.



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	2006.10.20	TITLE		GROUND TERMINAL		DWG. NO.		GND-27		PART NO.		GND-27TP		
	DRAWN	KEVIN		MATERIAL		BRASS		SIZE		A4		SPEC. DWG		REV	
	CHECKED	李柏青		COLOR		FINISH	TIN PLATED								
	APPROVED	Kang		UNLESS OTHERWISE SPECIFIED TOLERANCE:		SEE ABOVE		SCALE: 4:1		UNIT		mm			