




成型尺寸	公差
5mm 以下	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm 以上	±1.0

REVISIONS			
REV	DESCRIPTION	DATE	BY



MOUNTING HOLE
THICKNESS=0.8mm

QMFZ2 Component - Plastics

Friday, October 24, 2003

E162823

FORMOSA CHEMICALS & FIBRE CORP

PLASTICS DIV 201 TUNG HWA N RD TAIPEI 105 TAIWAN

Material Designation: AG15E1

Product Description: Acrylonitrile Butadiene Styrene (ABS), designated "TAIRLAC" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.6	HB	5	0	60	60	60	-	-
	3	-	-	-	60	60	60	-	-
	CTI: 0		HVTR: 0			D495: 6			

Dielectric Strength (kV/mm): -

Volume Resistivity (10¹¹ ohm-cm): -

Dimensional Stability(%): -

ISO Tensile Strength (MPa): -

ISO Flexural Strength (MPa): -

ISO Heat Deflection (°C): -

ISO Tensile Impact (kJ/m²): -

ISO Izod Impact (kJ/m²): -

ISO Charpy Impact (kJ/m²): -

Report Date: 11/1/1995

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

 <p>康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.</p>		TITLE	USB護蓋	產品規格圖面			
		MATERIAL	ABS UL94HB	DATE	2008.02.13		
		FINISH		DRAWN	BUNNY		
		COLOR	BLACK	CHECK	宋萍		
PART NUMBER	USBC-6	DRAWING NUMBER	USBC-6	UNLESS OTHERWISE SPECIFIED TOLERANCE	SEE ABOVE	APPROVED	Kang
SIZE	A4	SCALE	2:1	UNIT	mm	REV	A