




HOLE IN P.C.B  
THICKNESS: 1.4~1.8mm



HOLE IN P.C.B  
THICKNESS: 2.83~3.47mm

NOTE:1. SHRINKING IS NORMAL STATUS.

內縮為正常現象。

2. MADE OF EQUIVALENT MATERIAL.

均可使用同等材質。

3. THE COLOR BATCH TEST REPORT IS ONLY FOR FIRST LOT TEST.

色母環保檢測報告, 僅提供原始測試報告。

**K**  
 ISO 9001  
 ISO 14001  
 IATF 16949

康揚企業股份有限公司  
 KANG YANG HARDWARE ENTERPRISE CO., LTD.  
 康揚塑膠(東莞)有限公司  
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.  
 康哲電腦配件(吳江)有限公司  
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED.  DO NOT SCALE DRAWING	DATE	2021.11.01	TITLE	SPACER SUPPORT		DWG. NO.	PART NO.	
	DRAWN	Terry	MATERIAL	NYLON 66 UL94V-2		ULCSF-6.6XXL	ULCSF-6.6XXLB	
	CHECKED	林祺翔	COLOR	BLACK	FINISH			
	APPROVED	Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE:	SEE ABOVE		SIZE	A4	SPEC. DWG.
					SCALE: 3:1	UNIT	mm	SHEET 1 OF 1