



RECOMMEND MOUNTING HOLE  
RECOMMEND THICKNESS: 0.8mm

RECOMMEND LED

- NOTE: 1. SUITABLE FOR  $\phi 3$  LED WITH VISOR AND 2PIN.  
適用於  $\phi 3$  LED 有帽緣的，適用於 2PIN。  
2. SHRINKING IS NORMAL STATUS.  
內縮為正常現象。  
3. MADE OF EQUIVALENT MATERIAL.  
均可使用同等材質。  
4. THE COLOR BATCH TEST REPORT IS ONLY FOR TEST PURPOSE.  
色母環保檢測報告，僅提供原始測試報告。



康揚企業股份有限公司  
KANG YANG HARDWARE ENTERPRISE CO., LTD.  
康揚塑膠(東莞)有限公司  
KANG YANG PLASTIC(DONG GUAN)CO.,LTD.  
康哲電腦配件(吳江)有限公司  
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	2023.09.18	TITLE		LED HOLDER		DWG. NO.	PART NO.			
	DRAWN	K.W	MATERIAL		NYLON66 UL94V-0		LED3-64		LED3-64VB		
	CHECKED	Kenny	COLOR	BLACK	FINISH		SIZE	A4	SPEC. DWG	REV	A
	APPROVED	Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE:		SEE ABOVE		SCALE:	5:1	UNIT	mm	SHEET