



MOUNTING HOLE: $\phi 2.54 \pm 0.05\text{mm}$
 THICKNESS: 1.63mm(MAX)
 (RECOMMEND FOR REFERENCE ONLY)

NOTE: MADE OF PLASTIC OR EQUIVALENT MATERIALS.
 塑膠製品或同等材質.



ISO 9001
 ISO 14001
 QC 080000
 IATF 16949

康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

康揚塑膠五金(泰國)有限公司
 บริษัท ตั้ง ทวาง ฮาร์ดแวร์ (ไทยแลนด์) จำกัด
 KANG YANG HARDWARE (THAILAND) CO., LTD.
 康揚越南有限公司
 CÔNG TY TNHH KANG YANG VIỆT NAM
 KANG YANG VIETNAM CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	TITLE	DWG. NO.	PART NO.
	2024.06.21	PCB SPACER	MAMS-HL	MAMS-6.4L
	DRAWN	MATERIAL	SIZE	SPEC. DWG.
	C.S.L	NYLON 66(PA66) UL94V-2	A4	
CHECKED	COLOR	FINISH	REV	
林祺翔	NATURAL		A	
APPROVED	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE		SCALE: 4:1	UNIT mm
Xuping 代				SHEET 1 OF 1