


NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.  
 鍍錫最佳使用時間，為製造日起 3 個月內。  
 2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.  
 表面為鍍錫，未使用完畢時，產品請密封。

MOUNTING HOLE  
 (RECOMMEND FOR REFERENCE ONLY)



康揚企業股份有限公司  
 KANG YANG HARDWARE ENTERPRISE CO., LTD.  
 康揚塑膠(東莞)有限公司  
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.  
 康哲電腦配件(吳江)有限公司  
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

康揚塑膠五金(泰國)有限公司  
 บริษัท ตั้ง ทวาย ฮาร์ดแวร์ (ไทยแลนด์) จำกัด  
 KANG YANG HARDWARE (THAILAND) CO., LTD.  
 康揚越南有限公司  
 CÔNG TY TNHH KANG YANG VIỆT NAM  
 KANG YANG VIETNAM CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	2025.04.01	TITLE	P.C.B TERMINAL	DWG. NO.	PCB-135	PART NO.	PCB-135
	DRAWN	Howl	MATERIAL	BRASS	SIZE	A4	SPEC. DWG.	REV
	CHECKED	[Signature]	COLOR		FINISH	TIN PLATED		A
	APPROVED	[Signature]	UNLESS OTHERWISE SPECIFIED TOLERANCE:	SEE ABOVE	SCALE:	2:1	UNIT	mm