


MOUNTING HOLE:  $\phi 3.1 \sim 3.3$   
 THICKNESS: 6.1~6.7mm  
 (RECOMMEND FOR REFERENCE ONLY)

- NOTE: 1. SHRINKING IS NORMAL STATUS.  
 內縮為正常現象。  
 2. MADE OF EQUIVALENT MATERIAL.  
 均可使用同等材質。  
 3. THE COLOR BATCH TEST REPORT IS ONLY FOR FIRST LOT TEST.  
 色母環保檢測報告, 僅提供原始測試報告。



康揚企業股份有限公司  
 KANG YANG HARDWARE ENTERPRISE CO., LTD.  
 康揚塑膠(東莞)有限公司  
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.  
 康哲電腦配件(吳江)有限公司  
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

康揚塑膠五金(泰國)有限公司  
 บริษัท ห้าง พยาง ฮาร์ดแวร์ (ไทยแลนด์) จำกัด  
 KANG YANG HARDWARE (THAILAND) CO., LTD.  
 康揚越南有限公司  
 CÔNG TY TNHH KANG YANG VIỆT NAM  
 KANG YANG VIETNAM CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	TITLE		DWG. NO.		PART NO.	
	2024.03.18	SNAP RIVET		SRCC-12L		SRCC-12L	
	DRAWN	MATERIAL		SIZE	SPEC. DWG.	REV	A
	Terry	NYLON 66 UL94V-2					
CHECKED	COLOR	FINISH	SCALE: 4:1	UNIT	mm	SHEET 1 OF 1	
Yuping	BLACK						
APPROVED	UNLESS OTHERWISE SPECIFIED TOLERANCE:		SEE ABOVE				
Kang							