



DIM	TOL
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	±1.0



PART NO.	A	B
TP632-5	5.0	3.0
TP632-5.5	5.5	3.5
TP632-6	6.0	4.0
TP632-6.3	6.3	4.0
TP632-8	8.0	6.0
TP632-9	9.0	6.0
TP632-9.5	9.5	6.0
TP632-10	10.0	6.0
TP632-11	11.0	6.0
TP632-12	12.0	6.0
TP632-12.7	12.7	6.0
TP632-15.9	15.9	6.0
TP632-19.1	19.1	6.0
TP632-25.4	25.4	6.0
TP632-31.8	31.8	6.0

NOTE:1. INNER THREAD WAS DONE BY 2ND PROCESS TAPING. SONE SLIGHT NYLON BURRS REMAINED INSIDE THE THREAD HOLE IS A NORMAL PHENOMENON.

此為二次攻牙, 因為尼龍材質緣故. 故穴孔有些許尼龍屑, 屬正常現象.
2. MADE OF EQUIVALENT MATERIAL.
可使用同等材質.



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE 2007.03.19	TITLE THREADED SPACER	DWG. NO. TP632-H		PART NO. SEE ABOVE	
	DRAWN JOHNNY	MATERIAL NYLON 66 UL94V-2				
	CHECKED 李柏青	COLOR NATURAL	FINISH	SIZE A4	SPEC. DWG.	REV C
	APPROVED Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE		SCALE: NONE	UNIT mm	SHEET 1 OF 1